

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

6

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : C11D 3/37, 3/43, 1/94, 3/10, 3/20, 3/30	A1	(11) International Publication Number: WO 97/33963 (43) International Publication Date: 18 September 1997 (18.09.97)
(21) International Application Number: PCT/US97/03388 (22) International Filing Date: 5 March 1997 (05.03.97) (30) Priority Data: 08/615,375 14 March 1996 (14.03.96) US (71) Applicant: THE PROCTER & GAMBLE COMPANY [US/US]; One Procter & Gamble Plaza, Cincinnati, OH 45202 (US). (72) Inventors: WILLEY, Alan, David; 1071 Celestial Street, Cincinnati, OH 45242 (US). MASTERS, Ronald, Anthony; 2300 Catalpa Drive, Loveland, OH 45140 (US). MAILE, Michael, Stephen; 2870 Mossybrink Court, Maineville, OH 45039 (US). (74) Agents: REED, T., David et al.; The Procter & Gamble Company, 5299 Spring Grove Avenue, Cincinnati, OH 45217 (US).		(81) Designated States: CA, CN, JP, MX, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
(54) Title: GLASS CLEANER COMPOSITIONS HAVING GOOD FILMING/STREAKING CHARACTERISTICS CONTAINING AMINE OXIDE POLYMERS FUNCTIONALITY (57) Abstract Aqueous, liquid hard surface detergent compositions having improved cleaning and good filming/streaking characteristics contain an amine oxide polymer at critical levels. Preferred formulas contain an amount of PVNO effective to provide an improvement in spotting/filming after at least three rewettings of the glass; hydrophobic solvent; detergent surfactant selected from the group consisting of anionic surfactants, amphoteric detergent surfactants including zwitterionic surfactants; and mixtures thereof; and the balance being an aqueous solvent system comprising water and, optionally, non-aqueous polar solvent.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

GLASS CLEANER COMPOSITIONS HAVING GOOD FILMING/STREAKING
CHARACTERISTICS CONTAINING AMINE OXIDE POLYMERS
FUNCTIONALITY

5

FIELD OF INVENTION

10 This invention pertains to glass cleaning compositions, preferably liquid detergent compositions for use in cleaning glass, especially window glass, and, preferably, other hard surfaces. Such compositions typically contain detergent surfactants, solvents, builders, etc.

BACKGROUND OF THE INVENTION

15 The use of, e.g., solvents and organic water-soluble synthetic detergent surfactants at low levels for cleaning glass are known. There are several compositions known that provide good filming/streaking characteristics so that the glass is cleaned without leaving objectionable levels of spots and/or films.

20 Known detergent compositions comprise certain organic solvents, detergent surfactants, and optional builders and/or abrasives. The prior art, however, fails to teach, or recognize, the advantage of providing an amine oxide polymer material in glass cleaner formulations to provide a residual hydrophilicity.

The preferred liquid cleaning compositions have the great advantage that they can be applied to hard surfaces in neat or concentrated form so that a relatively high level of, e.g., surfactant material and/or organic solvent is delivered directly to the soil. Therefore, 25 liquid cleaning compositions have the potential to provide superior soap scum, grease, and oily soil removal over dilute wash solutions prepared from powdered cleaning compositions. The most preferred compositions are those that provide good cleaning on tough soils and yet clean glass without leaving objectionable levels of spots and/or films.

30 Liquid cleaning compositions, and especially compositions prepared for cleaning glass, need exceptionally good filming/streaking properties. In addition, they can suffer problems of product form, in particular, inhomogeneity, lack of clarity, or excessive "solvent" odor for consumer use.

SUMMARY OF THE INVENTION

35 The present invention relates to detergent compositions that can clean glass without leaving objectionable levels of filming and/or streaking and which contain an

effective amount of amine-oxide polymer which provides the glass, especially window glass, with long lasting higher hydrophilicity. Preferably, said compositions are in the form of an aqueous, liquid, hard surface detergent composition having improved cleaning and good spotting characteristics after rewetting comprising: (A) an amount of water
5 soluble amine oxide polymer effective to provide an improvement in spotting/filming after at least three rewettings of the glass; (B) hydrophobic solvent; (C) detergent surfactant selected from the group consisting of anionic surfactants, amphoteric detergent surfactants including zwitterionic surfactants; and mixtures thereof; and (D) the balance
10 being an aqueous solvent system comprising water and, optionally, non-aqueous polar solvent with only minimal cleaning action selected from the group consisting of methanol, ethanol, isopropanol, ethylene glycol, polypropylene glycol, glycol ethers having a hydrogen bonding parameter of greater than 7.7, and mixtures thereof and any minor ingredients.

The compositions can be formulated at usage concentrations, or as concentrates,
15 either solid, or liquid, and can be packaged in a container having means for creating a spray to make application to hard surfaces more convenient.

All percentages, parts, and ratios herein are "by weight" and all amounts are approximations, unless otherwise stated.

DETAILED DESCRIPTION OF THE INVENTION


20 In accordance with the present invention, it has been found that superior detergent compositions for cleaning shiny surfaces such as glass which leave said surface with a desirable appearance, i.e., without objectionable levels of filming and/or streaking, can be further improved to help maintain said desirable appearance for an extended period of time by incorporating an amine oxide polymer which is substantive to said surfaces and
25 which provides a more hydrophilic surface. When such surfaces are rewetted, e.g., as when windows are wetted by rain, the water "sheets" off the surface and the surface is still without objectionable levels of spotting (and/or filming) after the surface dries. As anyone who has cleaned windows can attest, one of the most frustrating things that can happen after windows have been cleaned is for a rain shower to occur and leave spots on
30 the just cleaned window. The present invention meets a long felt need. The preferred aqueous liquid detergent compositions for cleaning shiny surfaces such as glass contain: (A) an amount of amine oxide polymer effective to provide an improvement in spotting/filming after at least three rewettings of the glass; (B) hydrophobic solvent; (C)
35 detergent surfactant selected from the group consisting of anionic surfactants, amphoteric detergent surfactants including zwitterionic surfactants; and mixtures thereof; and (D) the

balance being an aqueous solvent system comprising water and, optionally, n n-aqueous polar solvent with only minimal cleaning action selected from the group consisting of methanol, ethanol, isopropanol, ethylene glycol, polypropylene glycol, glycol ethers having a hydrogen bonding parameter of greater than 7.7, and mixtures thereof and any
 5 minor ingredients.

A. WATER SOLUBLE AMINE OXIDE POLYMER

An essential part of this invention is the substantive material that improves the hydrophilicity of the surface being treated, especially glass. This increase in hydrophilicity provides improved appearance when the surface is rewetted and then dried.
 10 The water "sheets" off the surface and thereby minimizes the formation of, e.g., "rainspots" that form upon drying. The use of polycarboxylate, polystyrene sulfonate, and polyether based polymers to provide this hydrophilicity is known in the art. The use of these polymers is described in P&G Copending Application Serial No. 08/378,205, filed January 25, 1995, Masters, et al., which is herein incorporated by reference.
 15 However, the use of relatively low molecular weight, water soluble amine oxide polymers to achieve improved hydrophilicity in a glass cleaner has heretofore not been disclosed in the art.

While as not to be limited by theory, it is believed that the partial positive charge of the amine oxide group acts to adhere the polymer to the surface of the glass. It is further
 20 believed that the adhesion of these polymers alters the surface properties of the glass thus allowing water to "sheet" more readily. The polymers of this invention have one or more monomeric units containing at least one N-oxide group. At least about 10%, preferably more than about 50%, more preferably greater than about 90% of said monomers forming said polymers contain an amine oxide group. These polymers can be described by the
 25 general formula:




wherein each P is selected from homopolymerizable and copolymerizable moieties which attach to form the polymer backbone, preferably vinyl moieties, e.g. C(R)₂-C(R)₂, wherein each R is H, C₁-C₁₂ (preferably C₁-C₄) alkyl(ene), C₆-C₁₂ aryl(ene) and/or B; B is
 30 a moiety selected from substituted and unsubstituted, linear and cyclic C₁-C₁₂ alkyl, C₁-C₁₂ alkylene, C₁-C₁₂ heterocyclic, aromatic C₆-C₁₂ groups and wherein at least one of said

B moieties has at least one amine oxide ($\equiv N \rightarrow O$) group present; u is from 0 to about 2; and t is number such that the average molecular weight of the polymer is from about 2,000 to about 100,000, preferably from about 5,000 to about 20,000, and more preferably from about 8,000 to about 12,000.

- 5 The preferred polymers of this invention possess the unexpected property of being substantive without leaving a visible residue that would render the glass surface unappealing to consumers. The preferred polymers include poly(4-vinylpyridine N-oxide) polymers (PVNO), e.g. those formed by polymerization of monomers that include the following moiety:

10



- wherein, for the purposes of this invention, t is a number such that the average molecular weight of the polymer is from about 2,000 to about 100,000, preferably from about 5,000 to about 20,000, and more preferably from about 8,000 to about 12,000. The desirable
15 molecular weight range of polymers useful in the present invention stands in contrast to that found in the art relating to polycarboxylate, polystyrene sulfonate, and polyether based additives which prefer molecular weights in the range of 400,000 to 1,500,000.

- The level of amine oxide polymer should normally be from about 0.01% to about 1%, preferably from about 0.05% to about 0.5%, more preferably from about 0.1% to
20 about 0.3%, by weight of the composition.

B. HYDROPHOBIC SOLVENT

- In order to improve cleaning in liquid compositions, one can use a hydrophobic solvent that has cleaning activity. The solvents employed in the hard surface cleaning compositions herein can be any of the well-known "degreasing" solvents commonly used
25 in, for example, the dry cleaning industry, in the hard surface cleaner industry and the metalworking industry.

A useful definition of such solvents can be derived from the solubility parameters as set forth in "The Hoy," a publication of Union Carbide, incorporated herein by

reference. The most useful parameter appears to be the hydrogen bonding parameter which is calculated by the formula:

$$\gamma_H = \gamma_T \left[\frac{\alpha - 1}{\alpha} \right]^{1/2}$$

5

wherein γ_H is the hydrogen bonding parameter, α is the aggregation number,

$$(\text{Log } \alpha = 3.39066 \frac{T_b}{T_c} - 0.15848 - \text{Log } \frac{M}{d}), \text{ and}$$

10 γ_T is the solubility parameter which is obtained from the formula:

$$\gamma_T = \left[\frac{(\Delta H_{25} - RT)d}{M} \right]^{1/2}$$

15 where ΔH_{25} is the heat of vaporization at 25°C, R is the gas constant (1.987 cal/mole/deg), T is the absolute temperature in °K, T_b is the boiling point in °K, T_c is the critical temperature in °K, d is the density in g/ml, and M is the molecular weight.

For the compositions herein, hydrogen bonding parameters are preferably less than about 7.7, more preferably from about 2 to about 7, or 7.7, and even more preferably from about 3 to about 6. Solvents with lower numbers become increasingly difficult to solubilize in the compositions and have a greater tendency to cause a haze on glass.
20 Higher numbers require more solvent to provide good greasy/oily soil cleaning.

Hydrophobic solvents are typically used at a level of from about 0.5% to about 30%, preferably from about 2% to about 15%, more preferably from about 3% to about 8%. Dilute compositions typically have solvents at a level of from about 1% to about 10%, preferably from about 3% to about 6%. Concentrated compositions contain from
25 about 10% to about 30%, preferably from about 10% to about 20% of solvent.

Many of such solvents comprise hydrocarbon or halogenated hydrocarbon moieties of the alkyl or cycloalkyl type, and have a boiling point well above room temperature, i.e., above about 20°C.

30 The formulator of compositions of the present type will be guided in the selection of cosolvent partly by the need to provide good grease-cutting properties, and partly by

aesthetic considerations. For example, kerosene hydrocarbons function quite well for grease cutting in the present compositions, but can be malodorous. Kerosene must be exceptionally clean before it can be used, even in commercial situations. For home use, where malodors would not be tolerated, the formulator would be more likely to select
5 solvents which have a relatively pleasant odor, or odors which can be reasonably modified by perfuming.

The C₆-C₉ alkyl aromatic solvents, especially the C₆-C₉ alkyl benzenes, preferably octyl benzene, exhibit excellent grease removal properties and have a low, pleasant odor. Likewise, the olefin solvents having a boiling point of at least about
10 100°C, especially alpha-olefins, preferably 1-decene or 1-dodecene, are excellent grease removal solvents.

Generically, glycol ethers useful herein have the formula R¹¹ O-(R¹²O)_m H wherein each R¹¹ is an alkyl group which contains from about 3 to about 8 carbon atoms, each R¹² is either ethylene or propylene, and m¹ is a number from 1 to about 3. The
15 most preferred glycol ethers are selected from the group consisting of monopropyleneglycolmonopropyl ether, dipropyleneglycolmonobutyl ether, monopropyleneglycolmonobutyl ether, ethyleneglycolmonohexyl ether, ethyleneglycolmonobutyl ether, diethyleneglycolmonohexyl ether, monoethyleneglycolmonohexyl ether, monoethyleneglycolmonobutyl ether, and mixtures
20 thereof.


A particularly preferred type of solvent for these hard surface cleaner compositions comprises diols having from 6 to about 16 carbon atoms in their molecular structure. Preferred diol solvents have a solubility in water of from about 0.1 to about 20 g/100 g of water at 20°C.

25 Solvents such as pine oil, orange terpene, benzyl alcohol, n-hexanol, phthalic acid esters of C₁₋₄ alcohols, butoxy propanol, Butyl Carbitol® and 1(2-n-butoxy-1-methylethoxy)propane-2-ol (also called butoxy propoxy propanol or dipropylene glycol monobutyl ether), hexyl diglycol (Hexyl Carbitol®), butyl triglycol, diols such as 2,2,4-trimethyl-1,3-pentanediol, and mixtures thereof, can be used. The butoxy-propanol
30 solvent should have no more than about 20%, preferably no more than about 10%, more preferably no more than about 7%, of the secondary isomer in which the butoxy group is attached to the secondary atom of the propanol for improved odor.


C) THE DETERGENT SURFACTANT(1) The Amphocarboxylate Detergent Surfactant

The aqueous, liquid hard surface detergent compositions (cleaners) herein can contain from about 0.001% to about 2%, preferably from about 0.01% to about 0.5%, more preferably from about 0.02% to about 0.2%, and even more preferably from about 0.03% to about 0.08%, of C₆₋₁₀ short chain amphocarboxylate detergent surfactant. It has been found that these amphocarboxylate, and, especially glycinate, detergent surfactants provide good cleaning with superior filming/streaking for detergent compositions that are used to clean both glass and/or relatively hard-to-remove soils. Despite the short chain, the detergency is good and the short chains provide improved filming/streaking, even as compared to most of the zwitterionic detergent surfactants described hereinafter. Depending upon the level of cleaning desired and/or the amount of hydrophobic material in the composition that needs to be solubilized, one can either use only the amphocarboxylate detergent surfactant, or can combine it with cosurfactant, preferably said zwitterionic surfactants.

The "amphocarboxylate" detergent surfactants herein preferably have the generic formula:




wherein R is a C₆₋₁₀ hydrophobic moiety, typically a fatty acyl moiety containing from about 6 to about 10 carbon atoms which, in combination with the nitrogen atom forms an amido group, R¹ is hydrogen (preferably) or a C₁₋₂ alkyl group, R² is a C₁₋₃ alkyl or, substituted C₁₋₃ alkyl, e.g., hydroxy substituted or carboxy methoxy substituted, preferably, hydroxy ethyl, each n is an integer from 1 to 3, each p is an integer from 1 to 2, preferably 1, and each M is a water-soluble cation, typically an alkali metal, ammonium, and/or alkanolammonium cation. Such detergent surfactants are available, for example: from Witco under the trade name Rewoteric AM-V®, having the formula



30 Mona Industries, under the trade name Monateric 1000®, having the formula



and Lonza under the trade name Amphoterger KJ-2®, having the formula



35 (2) Zwitterionic Detergent Surfactant

The aqueous, liquid hard surface detergent compositions (cleaners) herein can contain from about 0.001% to about 2% of suitable zwitterionic detergent surfactant containing a cationic group, preferably a quaternary ammonium group, and an anionic group, preferably carboxylate, sulfate and/or sulfonate group, more preferably sulfonate.

5 A more preferred range of zwitterionic detergent surfactant inclusion is from about 0.02% to about 1% of surfactant, a most preferred range is from about 0.05% to about 0.2%.

Zwitterionic detergent surfactants, as mentioned hereinbefore, contain both a cationic group and an anionic group and are in substantial electrical neutrality where the number of anionic charges and cationic charges on the detergent surfactant molecule are

10 substantially the same. Zwitterionic detergents, which typically contain both a quaternary ammonium group and an anionic group selected from sulfonate and carboxylate groups are desirable since they maintain their amphoteric character over most of the pH range of interest for cleaning hard surfaces. The sulfonate group is the preferred anionic group.

Preferred zwitterionic detergent surfactants have the generic formula:

15



wherein each Y is preferably a carboxylate (COO⁻) or sulfonate (SO₃⁻) group, more preferably sulfonate; wherein each R³ is a hydrocarbon, e.g., an alkyl, or alkylene, group

20 containing from about 8 to about 20, preferably from about 10 to about 18, more preferably from about 12 to about 16 carbon atoms; wherein each (R⁴) is either hydrogen, or a short chain alkyl, or substituted alkyl, containing from one to about four carbon atoms, preferably groups selected from the group consisting of methyl, ethyl, propyl, hydroxy substituted ethyl or propyl and mixtures thereof, preferably methyl; wherein each

25 (R⁵) is selected from the group consisting of hydrogen and hydroxy groups with no more than one hydroxy group in any (CR⁵)₂ group; wherein (R⁶) is like R⁴ except preferably not hydrogen; wherein m is 0 or 1; and wherein each n¹ and p¹ are an integer from 1 to about 4, preferably from 2 to about 3, more preferably about 3. The R³ groups can be branched, unsaturated, or both and such structures can provide filming/streaking

30 benefits, even when used as part of a mixture with straight chain alkyl R³ groups. The R⁴ groups can also be connected to form ring structures such as imidazoline, pyridine, etc. Preferred hydrocarbyl amidoalkylene sulfobetaine (HASB) detergent surfactants wherein m = 1 and Y is a sulfonate group provide superior grease soil removal and/or filming/streaking and/or "anti-fogging" and/or perfume solubilization properties. Such

35 hydrocarbylamidoalkylene sulfobetaines, and, to a lesser extent hydrocarbylamidoalkylene betaines are excellent for use in hard surface cleaning

detergent compositions, especially those formulated for use on both glass and hard-to-remove soils. They are even better when used with monoethanolamine and/or specific beta-amino alkanol as disclosed herein.

5 A more preferred specific detergent surfactant is a C₁₀₋₁₄ fatty acylamidopropylene(hydroxypropylene)sulfobetaine, e.g., the detergent surfactant available from the Witco Company as a 40% active product under the trade name "REWOTERIC AM CAS Sulfobetaine®."

10 The level of zwitterionic detergent surfactant, e.g., HASB, in the composition is typically from about 0.001% to about 2.0%, preferably from about 0.02% to about 1.0%. The level in the composition is dependent on the eventual level of dilution to make the wash solution. It is an advantage of the zwitterionic detergent, e.g., HASB, that compositions containing it can be more readily diluted by consumers since it does not interact with hardness cations as readily as conventional anionic detergent surfactants. Zwitterionic detergents are also extremely effective at very low levels, e.g., below about 15 1%.

Other zwitterionic detergent surfactants are set forth at Col. 4 of U.S. Pat. No. 4,287,080, Siklosi, incorporated herein by reference. Another detailed listing of suitable zwitterionic detergent surfactants for the detergent compositions herein can be found in U.S. Pat. No. 4,557,853, Collins, issued Dec. 10, 1985, incorporated by reference herein. 20 Commercial sources of such surfactants can be found in McCutcheon's EMULSIFIERS AND DETERGENTS, North American Edition, 1984, McCutcheon Division, MC Publishing Company, also incorporated herein by reference.

(3) Anionic and Optional Nonionic Detergent Surfactant


25 The detergent compositions, preferably aqueous, liquid hard surface detergent compositions, herein can contain, as the cosurfactant, less preferred, or as the primary detergent surfactant, preferably, from about 0.001% to about 2.0%, preferably from about 0.01% to about 1.0% of suitable anionic detergent surfactant. The anionic surfactants are suitably water-soluble alkyl or alkylaryl compounds, the alkyl having from about 6 to about 20 carbons, and including a sulfate or sulfonate substituent group. Depending upon 30 the level of cleaning desired one can use only the anionic detergent surfactant, or the anionic detergent surfactant can be combined with a cosurfactant, preferably an amphoteric cosurfactant.

The anionic detergent surfactants herein preferably have the generic formula:



wherein R^9 is a C_6 - C_{20} alkyl chain, preferably a C_8 - C_{16} alkyl chain; R^{10} , when present, is a C_6 - C_{20} alkylene chain, preferably a C_8 - C_{16} alkylene chain, a C_6H_4 phenylene group, or O; and M is the same as before.

The most preferred compositions herein preferably contain from about 0.001% to about 2%, by weight of the composition, more preferably from about 0.01% to about 1%, most preferably from about 0.02% to about 0.3%, by weight of the composition, of one or more chainlengths of a linear alcohol sulfate detergent surfactant having the general formula:




wherein M is any suitable counterion, preferably sodium, potassium, etc.; and wherein R is an alkyl group with a chainlength of from about C_8 to about C_{18} and mixtures thereof, preferably from about C_{12} to about C_{18} and mixtures thereof, more preferably from about C_{14} to about C_{18} and mixtures thereof, and wherein R is C_{14} in more than about 30%, preferably more than about 35%, more preferably more than about 40%, by weight of the alkyl sulfate. The entire alkyl sulfate surfactant can contain R of C_{14} and longer chainlength(s), but more than 30%, by weight of the alkyl surfactant preferably must be a C_{14} chainlength. Compositions containing only alkyl sulfate surfactants with higher chainlengths, i.e., C_{16} - C_{18} provide good surface lubricity benefits. However, these chainlengths, without the required amount of C_{14} chainlengths, exhibit poor filming/streaking properties. On the other hand, compositions which are solely made up of lower-chain alkyl sulfate surfactants, i.e., C_8 - C_{12} alkyl sulfate surfactants, provide acceptable filming/streaking properties but show poor surface lubricity properties. The presence of the C_{14} chainlength at levels of more than about 30%, by weight of the alkyl sulfate surfactant, in combination with other chainlengths, or alone, provide a product with both excellent surface lubricity properties and excellent filming/streaking properties. Particularly preferred compositions contain from about 0.05% to about 0.30%, by weight of the composition, of a $C_{12/14}$ blend in which the C_{12} to C_{14} weight ratio is from about 1:10 to about 2:1, preferably from about 1:5 to about 1.5:1, and more preferably from about 1:3 to about 1:1. This combination has been found to provide sufficient surface lubricity while avoiding objectionable filming/streaking. The alcohol sulfate detergent raw materials selected are essentially free from unreacted fatty alcohol wherein the term "essentially free" is defined as having less than about 2%, by weight of the composition, preferably less than about 1.8%, and more preferably less than about 1.5%, by weight of the composition of unreacted fatty alcohol in a nominally 30% active raw material.

A most preferred alkyl sulfate surfactant is a mixture of Stepanol WA-Extra®, available from the Stepan Company, with extra C₁₄ alkyl sulfate added such that the C_{12/14} ratio is nearly 1:1.

Concentrated compositions can also be used in order to provide a less expensive product. When a higher concentration is used, i.e., when the level of alkyl sulfate surfactant used is from about 0.10% to about 2.0%, by weight of the composition, it is preferable to dilute the composition before using it to clean a hard surface, especially glass. Dilution ratios of the alkyl sulfate concentrate(s) to water can range, preferably, from about 1:1 to 1:10, more preferably from about 1:1.5 to 1:5, and most preferably from about 1:2 to 1:5.

Some suitable surfactants for use herein in small amounts are one or more of the following: sodium linear C₈-C₁₈ alkyl benzene sulfonate (LAS), particularly C₁₁-C₁₂ LAS; the sodium salt of a coconut alkyl ether sulfate containing 3 moles of ethylene oxide; the adduct of a random secondary alcohol having a range of alkyl chain lengths of from 11 to 15 carbon atoms and an average of 2 to 10 ethylene oxide moieties, several commercially available examples of which are Tergitol® 15-S-3, Tergitol® 15-S-5, Tergitol® 15-S-7, and Tergitol® 15-S-9, all available from Union Carbide Corporation; the sodium and potassium salts of coconut fatty acids (coconut soaps); the condensation product of a straight-chain primary alcohol containing from about 8 carbons to about 16 carbon atoms and having an average carbon chain length of from about 10 to about 12 carbon atoms with from about 4 to about 8 moles of ethylene oxide per mole of alcohol; an amide having one of the preferred formulas:



wherein R⁷ is a straight-chain alkyl group containing from about 7 to about 15 carbon atoms and having an average carbon chain length of from about 9 to about 13 carbon atoms and wherein each R⁸ is a hydroxy alkyl group containing from 1 to about 3 carbon atoms; a zwitterionic surfactant having one of the preferred formulas set forth hereinafter; or a phosphine oxide surfactant. Another suitable class of surfactants is the fluorocarbon surfactants, examples of which are FC-129®, a potassium fluorinated alkylcarboxylate and FC-170-C®, a mixture of fluorinated alkyl polyoxyethylene ethanols, both available from 3M Corporation, as well as the Zonyl® fluorosurfactants, available from DuPont Corporation. It is understood that mixtures of various surfactants can be used.

Nonionic surfactants, e.g., ethoxylated alcohols and/or alkyl phenols, can also be used as cosurfactants.

(4) Mixtures

Mixtures of amphocarboxylate, zwitterionic detergent surfactants, and/or anionic detergent surfactants as discussed hereinbefore, can be present in the present invention. The zwitterionic detergent surfactants can be present at levels from about 0.02% to about 15%. The amphocarboxylate detergent surfactants can be present at levels from about 0.001% to about 15%. The ratio of zwitterionic detergent surfactant to amphocarboxylate detergent surfactant is typically from about 3:1 to about 1:3, preferably from about 2:1 to about 1:2, more preferably about 1:1. The ratio of primary detergent surfactant to cosurfactant, or cosurfactants, is typically from about 3:1 to about 1:1.

(D) AQUEOUS SOLVENT SYSTEM

The balance of the formula is typically water and non-aqueous polar solvents with only minimal cleaning action like methanol, ethanol, isopropanol, ethylene glycol, glycol ethers having a hydrogen bonding parameter of greater than 7.7, propylene glycol, and mixtures thereof, preferably ethanol. The level of non-aqueous polar solvent is usually greater when more concentrated formulas are prepared. Typically, the level of non-aqueous polar solvent is from about 0.5% to about 40%, preferably from about 1% to about 10%, more preferably from about 2% to about 8% (especially for "dilute" compositions) and the level of water is from about 50% to about 99%, preferably from about 75% to about 95%.

(E) OPTIONAL INGREDIENTS

(1) Optional soluble carbonate and/or bicarbonate salts

Water-soluble alkali metal carbonate and/or bicarbonate salts, such as sodium bicarbonate, potassium bicarbonate, potassium carbonate, cesium carbonate, sodium carbonate, and mixtures thereof, are added to the composition of the present invention in order to improve the filming/streaking when the product is wiped dry on the surface, as is typically done in glass cleaning. Preferred salts are sodium carbonate, potassium carbonate, sodium bicarbonate, potassium bicarbonate, their respective hydrates, and mixtures thereof. Solubilized, water-soluble alkali metal carbonate and bicarbonate salts are typically present at a level of from about 0% to about 0.5%, preferably from about 0.005% to about 0.1%, more preferably from about 0.01% to about 0.1%, and most preferably from about 0.02% to about 0.05% by weight of the composition. The pH in the composition, at least initially, in use is from about 7 to about 11, preferably from

about 7.5 to about 10.5, more preferably from about 8 to about 10. pH is typically measured on the product.

(2) Optional tartaric acid / monoethanolamine salt

Detergent builders that are efficient for hard surface cleaners and have reduced
5 filming/streaking characteristics at the critical levels can also be employed in the present invention. Addition of the specific detergent builder tartaric acid at critical levels to the present composition improves cleaning without the problem of filming/streaking that usually occurs when detergent builders are added to hard surface cleaners. Through the present invention there is no longer the need to make a compromise between improved
10 cleaning and acceptable filming/streaking results which is especially important for hard surface cleaners which are also directed at cleaning glass. These compositions containing the detergent builder herein at the levels herein, have exceptionally good cleaning properties. They also have exceptionally good shine properties, i.e., when used to clean glossy surfaces, without rinsing, they have much less tendency than, e.g., carbonate built
15 products to leave a dull finish on the surface and filming/streaking.

The tartaric acid detergent builder is present at levels of from about 0.001% to about 0.1%, more preferably from about 0.01% to about 0.1%, and most preferably from about 0.01% to about 0.05%. The salts are preferably compatible and include ammonium, sodium, potassium and/or alkanolammonium salts. The alkanolammonium salt is
20 preferred. The preferred alkanolammonium salt is that formed by the addition of monoethanolamine (MEA) at a level of from about 0.005% to about 0.2%, preferably from about 0.01% to about 0.1%, more preferably from about 0.02% to about 0.1% by weight of the composition.

(F) OPTIONAL MINOR INGREDIENTS

25 The compositions herein can also contain other various adjuncts which are known to the art for detergent compositions. Preferably they are not used at levels that cause unacceptable filming/streaking. Non-limiting examples of such adjuncts are:

Hydrotropes such as sodium toluene sulfonate, sodium cumene sulfonate and potassium xylene sulfonate; and

30 Aesthetic-enhancing ingredients such as colorants and perfumes, providing they do not adversely impact on filming/streaking in the cleaning of glass. Most hard surface cleaner products contain some perfume to provide an olfactory aesthetic benefit and to cover any "chemical" odor that the product may have. The main function of a small fraction of the highly volatile, low boiling (having low boiling points), perfume
35 components in these perfumes is to improve the fragrance odor of the product itself.

rather than impacting on the subsequent odor of the surface being cleaned. However, some of the less volatile, high boiling perfume ingredients can provide a fresh and clean impression to the surfaces, and it is sometimes desirable that these ingredients be deposited and present on the dry surface. The perfumes are preferably those that are more water-soluble and/or volatile to minimize streaking and filming. The perfumes useful herein are described in more detail in U.S. Patent 5,108,660, Michael, issued April 28, 1992, at col. 8 lines 48 to 68, and col. 9 lines 1 to 68, and col. 10 lines 1 to 24, said patent, and especially said specific portion, being incorporated by reference.

Antibacterial agents can be present, but preferably only at low levels to avoid filming/streaking problems. More hydrophobic antibacterial/germicidal agents, like orthobenzyl-para-chlorophenol, are avoided. If present, such materials should be kept at levels below about 0.1%.

Stabilizing ingredients can be present typically to stabilize more of the hydrophobic ingredients, e.g., perfume. The stabilizing ingredients include acetic acid and propionic acids, and their salts, e.g., NH_4 , MEA, Na, K, etc., preferably acetic acid and the C_2 - C_6 alkane diols, more preferably butane diol. The stabilizing ingredients do not function in accordance with any known principle. Nonetheless, the combination of amido zwitterionic detergent surfactant with linear acyl amphocarboxylate detergent surfactant, anionic detergent surfactant, nonionic detergent surfactant, or mixtures thereof, and stabilizing ingredient can create a microemulsion. The amount of stabilizing ingredient is typically from about 0.01% to about 0.5%, preferably from about 0.02% to about 0.2%. The ratio of hydrophobic material, e.g., perfume that can be stabilized in the product is related to the total surfactant and typically is in an amount that provides a ratio of surfactant to hydrophobic material of from about 1:2 to about 2:1.

Other detergent builders that are efficient for hard surface cleaners and have reduced filming/streaking characteristics at the critical levels can also be present in the compositions of the invention.

Suitable additional optional detergent builders include salts of ethylenediaminetetraacetic acid (hereinafter EDTA), citric acid, nitrilotriacetic acid (hereinafter NTA), sodium carboxymethylsuccinic acid, sodium N-(2-hydroxypropyl)-iminodiacetic acid, and N-diethyleneglycol-N,N-diacetic acid (hereinafter DIDA). The salts are preferably compatible and include ammonium, sodium, potassium and/or alkanolammonium salts. The alkanolammonium salt is preferred as described hereinafter. A preferred detergent builder is NTA (e.g., sodium), a more preferred builder is citrate

(e.g., sodium or monoethanolamine), and a most preferred builder is EDTA (e.g., sodium).

These additional optional detergent builders, when present, are typically at levels of from about 0.05% to about 0.5%. more preferably from about 0.05% to about 0.3%, most preferably from about 0.05% to about 0.15%. The levels of these additional builders present in the wash solution used for glass should be less than about 0.2%. Therefore, typically, dilution is highly preferred for cleaning glass, while full strength is preferred for general purpose cleaning, depending on the concentration of the product.

Typically the best filming/streaking results occurs most when the builder is combined with amphoteric and/or zwitterionic detergent surfactant compositions although an improvement is also seen with the less preferred anionic or anionic/nonionic detergent surfactant compositions.

The invention is illustrated by the following nonlimiting Examples.

End Result Wipe Test

Procedure:

Five sprays of the product to be tested are applied to a 2ft. x 3ft. glass window (which can be soiled with body oils from a handprint) and wiped with two paper towels to near dryness, simulating actual consumer usage of the product.

Grading:

Expert judges are employed to evaluate the specific areas of product application for amount of filming/streaking, with the aid of a floodlight to simulate a sunbeam. A numerical value describing the quality of the end result is assigned to each product. For the test results reported here a 0-6 scale is used, in which 0 = good end result with no film/streak, and 6 = very poor end result.

EXAMPLE I

<u>INGREDIENT</u>	<u>Formula</u>	
	<u>1</u>	<u>2</u>
	<u>Wt.%</u>	<u>Wt.%</u>
Butoxypropanol	2.8	2.8
Ethanol	2.8	2.8
Sodium Dodecyl Sulfate	0.13	0.20 -
Sodium Tetradecyl Sulfate	0.11	0.08 -
NaHCO ₃	0.02	0
NaCO ₃	0.02	0
PVNO (avg MW ~ 10,000)	0.20	0

The above formulas were tested according to the above methods for end result wipe, with the results as follows (average of 7 different wiping habits):

Wiping Film/Streak Test

(avg. of 7 different wiping habits)

<u>Formula</u>	<u>Rating</u>
	(0 = good, 6 = poor)
1	1.15
2	1.39

These results show that the inclusion of the polymer does not harm film/streak. In fact, it is directionally better than the comparison formula.

Sheeting Test

The following test is used to determine the lasting effects of preventing water spots upon rewetting.

The windows, or mirrors, from the Filming/Streaking Test are rewetted by spraying with water containing about 0.02% household dust to simulate rain and dried, and this cycle is repeated twice more for a total of three cycles. The windows, or mirrors, are graded while wet using a scale in which 0 = No Sheeting and 6 = Heavy Sheeting.

The sheeting is indicative of the hydrophilicity and the resulting lack of spotting/filming when dry.

<u>Formula No.</u>	<u>Average Sheeting Grade</u>		
	<u>cycle 1</u>	<u>cycle 2</u>	<u>cycle 3</u>
1	6.0	6.0	5.3
2	3.7	0.5	0.0
Blank Glass	0.5	0.0	0.0

The above demonstrates the benefit of the polymer, when used at this level, in providing the sheeting (anti-spotting/filming) benefit upon rewetting.

The formulas are tested as in the above test for sheeting, but the samples are dried and graded for "rainspots" using the grading scale of the Filming/Streaking Test.

	<u>Formula No.</u>	<u>Average "Rainspot" Grade (0 = good, 6 = poor)</u>		
		<u>cycle 1</u>	<u>cycle 2</u>	<u>cycle 3</u>
	1	0.0	0.0	0.1
	2	1.0	3.1	4.2
5	Blank Glass	2.8	4.1	5.2

These results show the benefit of the polymer in helping prevent spots on windows even after 3 simulated rainstorms.

EXAMPLE II

10	<u>Component</u>	<u>Formula</u>				
		<u>3</u>	<u>4</u>	<u>5</u>	<u>6</u>	<u>7</u>
	Isopropanol	2.00	4.00			2.00
	Ethanol			2.00	5.00	
	Butoxypropanol	3.00	1.50	2.50	1.00	4.00
	C ₁₂ Alkyl Sulfate	0.20				
	C ₁₄ Alkyl Sulfate	0.08				0.10
	Cocoamidopropylbetaine		0.20			0.10
	Linear Alkyl (C ₈ -C ₁₈) Benzene Sulfonate			0.10		
	Sodium Laureth Sulfate				0.25	
	Alcohol Ethoxylate (Neodol® 91-6)			0.04		
	Sodium Bicarbonate		0.02		0.06	0.04
	Monoethanolamine			0.1		
	Tartaric Acid			0.03		
	PVNO (avg MW ~ 10,000)	0.10	0.15	0.25	0.30	0.20

WHAT IS CLAIMED IS:

1. Detergent composition that can clean glass without leaving objectionable levels of spots and/or films and which contains an amount, effective to provide the glass with long lasting higher hydrophilicity, of water soluble amine oxide polymer having an average molecular weight of from 2,000 to 100,000.

2. An aqueous, liquid, hard surface detergent composition according to Claim 1 having improved cleaning and good filming/streaking characteristics after rewetting and comprising:

- (A) an amount, effective to provide an improvement in spotting/filming after at least three rewettings of the glass, of water soluble amine oxide polymer,
- (B) hydrophobic solvent;
- (C) detergent surfactant selected from the group consisting of anionic surfactants, amphoteric detergent surfactants including zwitterionic surfactants; and mixtures thereof; and
- (D) the balance being an aqueous solvent system comprising water and, optionally, non-aqueous polar solvent with only minimal cleaning action selected from the group consisting of methanol, ethanol, isopropanol, ethylene glycol, polypropylene glycol, glycol ethers having a hydrogen bonding parameter of greater than 7.7, and mixtures thereof and any minor ingredients.

3. An aqueous liquid hard surface detergent composition according to Claim 1 or Claim 2 having excellent filming/streaking characteristics comprising:

- (A) from 0.01% to 1%, by weight of the composition, of amine oxide polymer, preferably poly(4-vinylpyridine N-oxide);
- (B) from 0.5% to 30%, by weight of the composition, of hydrophobic solvent, having a hydrogen bonding parameter of from 2 to 7.7;
- (C) detergent surfactant selected from the group consisting of:
 - (1) from 0.001% to 2% detergent surfactant having the generic formula :



wherein R is a C₆-C₁₀ hydrophobic moiety, including fatty acyl moiety containing from 6 to 10 carbon atoms which in combination with the nitrogen atom forms an amido group, R¹ is hydrogen or a C₁₋₂ alkyl group, R² is a C₁₋₂ alkyl, carboxymethoxy ethyl, or hydroxy ethyl, each n is an integer from 1 to 3, each p is an


integer from 1 to 2 and M is a water soluble cation selected from alkali metal, ammonium, alkanolammonium, and mixtures thereof cations;

(2) from 0.001% to 2% detergent surfactant having the generic formula:



wherein each R^3 is an alkyl, or alkylene, group containing from 10 to 18 carbon atoms, each (R^4) and (R^6) is selected from the group consisting of hydrogen, methyl, ethyl, propyl, hydroxy substituted ethyl or propyl and mixtures thereof, each (R^5) is selected from the group consisting of hydrogen and hydroxy groups, with no more than one hydroxy group in any $(CR^5)_2p1$ moiety; m is 0 or 1; each $n1$ and $p1$ is a number from 1 to 4; and Y is a carboxylate or sulfonate group; and

(3) from 0.001% to 2.0% detergent surfactant having the generic formula:



wherein R^9 is a C_6 - C_{20} alkyl chain; R^{10} is a C_6 - C_{20} alkylene chain, a C_6H_4 phenylene group, or O; and M is the same as before;

(4) from 0.01% to 0.3%, by weight of the composition, of a linear alkyl sulfate detergent surfactant having the general formula:



wherein M is a suitable counter ion; R^{11} is an alkyl group having a chain length of from C_8 to C_{18} or mixtures thereof; wherein more than 40%, by weight of said surfactant, of said surfactant has a C_{14} chainlength; and

(5) mixtures thereof; and

(D) the balance being an aqueous solvent system comprising water and, optionally, non-aqueous polar solvent with only minimal cleaning action selected from the group consisting of methanol, ethanol, isopropanol, ethylene glycol, polypropylene glycol, glycol ethers having a hydrogen bonding parameter of greater than 7.7, and mixtures thereof and any minor ingredients.

4. The composition of any of Claims 1-3 wherein the polymer (A) has an average molecular weight of from 5,000 to 20,000, preferably from 8,000 to 12,000.

5. The composition of any of Claims 1-4 wherein the polymer (A) is present at a concentration of 0.05% to 0.5% by weight of the composition.

6. The composition of any of Claims 1-5 further comprising from 0.005% to 0.1% of NaHCO_3 and from 0.005% to 0.1% Na_2CO_3 .
7. The composition of any of Claims 1-6 further comprising from 0.005% to 0.2% of monoethanolamine and from 0.005% to 0.1% tartaric acid.
8. The process of cleaning glass, that is subject to rewetting, with an effective amount of the composition of any of Claims 1-8 to provide anti-spotting/filming effects for at least three rewetting cycles.

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/US 97/03388

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 C11D3/37 C11D3/43 C11D1/94 C11D3/10 C11D3/20
C11D3/30

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 C11D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	EP 0 664 333 A (PROCTER & GAMBLE) 26 July 1995 see page 11, line 15 - line 21; claims 1-3,12,13 ---	1-5,8
Y	WO 96 04358 A (PROCTER & GAMBLE) 15 February 1996 see claims; example I & US 5 534 198 A cited in the application ---	1-5,8
A	EP 0 595 383 A (PROCTER & GAMBLE) 4 May 1994 see claim 10; examples ---	1-3
A	EP 0 647 706 A (CLOROX CO) 12 April 1995 see claims; examples -----	1-3

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

Date of the actual completion of the international search

30 June 1997

Date of mailing of the international search report

17. 07. 97

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (- 31-70) 340-2040, Tx. 31 651 epo nl,
Fax (- 31-70) 340-3016

Authorized officer

Loiselet-Taisne, S

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No.

PC./US 97/03388

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0664333 A	26-07-95	CN 1138874 A WO 9520031 A	25-12-96 27-07-95
WO 9604358 A	15-02-96	US 5534198 A AU 3103895 A CA 2196611 A FI 970431 A NO 970432 A	09-07-96 04-03-96 15-02-96 31-01-97 01-04-97
EP 0595383 A	04-05-94	AT 150077 T CA 2109188 A DE 69308726 D ES 2100444 T JP 6228590 A US 5536451 A	15-03-97 27-04-94 17-04-97 16-06-97 16-08-94 16-07-96
EP 0647706 A	12-04-95	US 5468423 A CA 2133889 A CN 1106454 A PL 305351 A US 5523024 A ZA 9407821 A	21-11-95 09-04-95 09-08-95 18-04-95 04-06-96 25-05-95